

INFRARED WIRELESS MICROPHONE

IR-200M(Y)

■DESCRIPTION

The IR-200M is a handheld infrared wireless microphone. It eliminates problems with interference or eavesdropping, allowing simultaneous use in adjacent conference rooms or school classrooms. Since infrared wireless microphone system uses a frequency band that does not interfere with that of the TS-800 and TS-900 series infrared conference system, both systems can be simultaneously installed in the same location.

SPECIFICATIONS

Battery	IR—200BT—2 rechargeable battery for the infrared wireless microphone (option)
,	or AA alkaline dry cell battery (2 pieces).
Current Consumption	Typ. 250 mA (2.4 V, Power selector switch: N)
	Typ. 340 mA (2.4 V, Power selector switch: H)
Infrared Emitter	
Wavelength	870 nm (AM: Brightness modulation)
Modulation Method	Frequency modulation
Carrier Frequency	Channel A: 3.100 MHz
	Channel B: 3.350 MHz
Transmission Distance	Approx. 20 m (65 ft) (Power selector switch: H, in an unobstructed space)
	Approx. 15 m (50 ft) (Power selector switch: N, in an unobstructed space)
Tone Signal	32.768 kHz
Modulation Sensitivity	± 4.8 kHz (1 kHz, when SPL of 84 dB is input)
Maximum Input Sound Pressure	120 dB SPL
Microphone Unit	Unidirectional electret condenser microphone
Frequency Response	100 Hz - 12 kHz
Preemphasis	300 μs
Battery Operation Time	Approx. 8 h (when the IR—200BT rechargeable battery for the infrared wireless
	microphone is used, Power selector switch: N)
	Approx. 6 h (when the alkaline battery is used, Power selector switch: N)
Operating Temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	30 % to 85 %RH
Finish	Control section: ABS resin, metallic gray, paint, 50% gloss
	Filter section: Polycarbonate, optical cut filter
Dimensions	Ø37 × 241.8 (H) mm (Ø1.46" × 9.52")
Weight	170 g (0.37 lb) (with battery)
Accessory	Screw driver (for setting) …1, Color label (6 colors) …1
Option	Battery charger: IR-200BC
	Ni-MH battery: IR-200BT-2 (containing 2 pieces)

■ APPEARANCE

