

■DESCRIPTION

The SC-P620-AS is a highly intelligible speaker with a built-in 20W digital power amplifier, that provides public address announcement and remote paging via network video surveillance applications. Its powder-coated finish and stainless steel screws ensure the unit's weatherproof capability.

■SPECIFICATIONS

0 dB = 1V

| | |
|-----------------------|--|
| Power Source | 12V DC, 2A (DC Socket "+" Type A : 5.5 x 2.1mm) |
| Power Consumption | 15W (1.25A) at Rated output |
| | 25W (2.10A) at Maximum output |
| Input | 0 dB*, 10kΩ, Unbalanced (RCA plug) |
| Signal Gain | 8, 16, 24 or 32db (Factory pre-set to 16db) |
| Volume Adjustment | Internal volume control (Factory pre-set to maximum position) |
| Sound Pressure Level | 113dB (1W, 1m at 500Hz to 2.5KHz peak level) |
| | Max. SPL (above 120dB) |
| Frequency Response | 250 - 10,000 Hz |
| Operating Temperature | -20°C to +55°C (must be free from dew condensation) |
| Dust/Water Protection | IP 65 |
| Finish | Horn Flare: HIPS resin, white (RAL9010 equivalent) |
| | Reflector horn and case: ABS resin, white (RAL9010 equivalent) |
| | Bracket, screws & bolts: Stainless steel |
| Cable Cord | Length: 2m Flying Lead (RCA plug) & DC socket ("+") |
| Dimesions | 292 (W) x 230 (H) x 280 (D) mm |
| Weight | Approx. 1.8 kg |
| Option | AD-5000-2 (LTE24E-S2-1) AC Adapter |

Notes: The design and specifications are subject to change without prior notice for improvement.

■APPEARANCE

